




EV45E

PERFORMANCE CHARACTERISTICS:


22 Kw/ 30 Hp Maximum Power
28—30 Rpm Cutter Speed Rotation
10mm, 12mm or 16 mm Shred Width
450 mm x 375 mm Cutting Chamber Opening
18,9 m/min Cutting Speed
1500 Kg per hour*
72 DbA @ 1 meter (no load)
Recommended In-feed: Bin Tipper or Conveyor Belt
Recommended Out-feed: Storage Bin or Conveyor Belt



* Normal Office Paper Under Ideal Conditions
Specifications are subject to change without notice. Contact your nearest distributor/ agent for up-to-date specifications prior to purchase.

EV45E

TECHNICAL SPECIFICATIONS:



PHYSICAL DIMENSIONS:

Total Height:	2180 mm
Total Length:	2570 mm
Total Width:	1000 mm
Ground Clearance (underneath shredder):	810 mm
Ground to Hopper Entrance Lip Height:	1815 mm
Hopper Opening:	930 x 800 mm
Shredder Chamber Opening:	450 x 375 mm

SHREDDER NAME:	EV45E (Electric)
Number of Motors	2 x 11Kw
Number of Gearboxes	2
Type of Gearboxes	Planetary Reduction
Cutter Width	10mm, 12mm or 16mm
No. of Hooks per cutter	3
Cutter Diameter	200mm
Distance between Shafts	165mm
Hex Shaft Diameter	77mm AF
Critical Shaft Length	450mm
Cutter Chamber Opening	450mm x 375mm
Cutting Chamber Height	250mm
Hopper Height	1000mm
Stand Height	930mm
Total Height	2180mm
Floor Footprint Dimensions	1000mm x 2570mm
Weight	1200 Kg
Capacity/ Throughput Rate	1500 kg per hour*

* Normal Office Paper Under Ideal Conditions

Specifications are subject to change without notice. Contact your nearest distributor/ agent for up-to-date specifications prior to purchase.